

IN THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) A method comprising:
starting a timer defined for use within a first wireless communication system; and
estimating [[a]] duration of ~~a transition from~~ transitions between the first wireless communication system [[to]] and a second wireless communication system as a function of the timer, each of the wireless communication systems being a voice/data system that conforms to a standard for at least one of CDMA, TDMA, FDMA, and GSM.
2. (Original) The method of claim 1, further comprising performing a pre-defined operation associated with the timer.
3. (Original) The method of claim 2, wherein the operation is pre-defined by the first wireless communication system.
4. (Original) The method of claim 1, wherein the timer comprises a supervision timer.
5. (Original) The method of claim 1, wherein the timer is defined by the IS856 wireless communication standard.
6. (Original) The method of claim 1, further comprising:
starting a plurality of timers defined for use within the first wireless communication system; and
when returning to the first wireless communication system, estimating the duration of the transition as a function of the plurality of timers.
7. (Original) The method of claim 1, wherein the first wireless communication system is an IS856 system and the second wireless communication system is an IS2000-1x system.

8. (Currently Amended) The method of claim 7, wherein the ~~supervision~~ timer comprises an IS856 Control Channel Supervision Timer.

9. (Currently Amended) ~~[[The]]~~ A method of claim 8, further comprising:
starting an IS856 Control Channel Supervision Timer defined for use within an
IS856 communication system;
estimating a duration of a transition from the IS856 communication system to an
IS2000-1x communication system as a function of the timer;
attempting to receive a synchronous control channel capsule; and
transitioning to a network acquisition state when the attempt to receive the
synchronous control channel capsule is unsuccessful.

10. (Currently Amended) The method of claim 7, wherein the ~~supervision~~ timer comprises a data rate control (DRC) supervision timer, the method further comprising:
starting a combination timer; and
when returning to the IS856 system, estimating the duration of the transition as a
function of the DRC supervision timer and the combination timer.

11. (Original) The method of claim 10, further comprising:
restarting a transmitter in response to expiration of the DRC supervision timer;
and
transitioning to an inactive state in response to expiration of the combination
timer.

12. (Currently Amended) A processor-readable medium containing processor
executable instructions for:
starting a timer defined for use within a first wireless communication system; and
estimating ~~[[a]]~~ duration of a transition from transitions between the first wireless
communication system ~~[[to]]~~ and a second wireless communication system as a function
of the timer, each of the wireless communication systems being a voice/data system that
conforms to a standard for at least one of CDMA, TDMA, FDMA, and GSM.

13. (Original) The processor-readable medium of claim 12, containing further instructions for performing a pre-defined operation associated with the timer.

14. (Original) The processor-readable medium of claim 13, wherein the operation is pre-defined by the first wireless communication system.

15. (Original) The processor-readable medium of claim 12, wherein the timer comprises a supervision timer.

16. (Original) The processor-readable medium of claim 12, wherein the timer is defined by the IS856 wireless communication standard.

17. (Original) The processor-readable medium of claim 12, containing further instructions for:

starting a plurality of timers defined for use within the first wireless communication system; and

when returning to the first wireless communication system, estimating the duration of the transition as a function of the plurality of timers.

18. (Original) The processor-readable medium of claim 12, wherein the first wireless communication system is an IS856 system and the second wireless communication system is an IS2000-1x system.

19. (Currently Amended) The processor-readable medium of claim 18, wherein the ~~supervision~~ timer comprises an IS856 Control Channel Supervision Timer.

20. (Currently Amended) ~~[[The]] A~~ processor-readable medium ~~of claim 19,~~ containing processor executable ~~further~~ instructions for:

starting an IS856 Control Channel Supervision Timer defined for use within an IS856 communication system;

estimating a duration of a transition from the IS856 communication system to an IS2000-1x communication system as a function of the timer;

attempting to receive a synchronous control channel capsule; and
transitioning to a network acquisition state when the attempt to receive the synchronous control channel capsule is unsuccessful.

21. (Currently Amended) The processor-readable medium of claim 18, wherein the ~~supervision~~-timer comprises a data rate control (DRC) supervision timer, the processor-readable medium containing further instructions for:

starting a combination timer; and
when returning to the IS856 system, estimating the duration of the transition as a function of the DRC supervision timer and the combination timer.

22. (Original) The processor-readable medium of claim 21, containing further instructions for:

restarting a transmitter in response to expiration of the DRC supervision timer;
and
transitioning to an inactive state in response to expiration of the combination timer.

23. (Currently Amended) A wireless communication device comprising:
first wireless communication system hardware for operating in a first wireless communication system;
second wireless communication system hardware for operating in a second wireless communication system;
an interoperation module to configure the wireless communication device in response to a transition between the first and second wireless communication systems, the interoperation module configured to estimate a duration of the transition as a function of a supervision timer, each of the wireless communication systems being a voice/data system that conforms to a standard for at least one of CDMA, TDMA, FDMA, and GSM.

24. (Original) The wireless communication device of claim 23, wherein the interoperation module is configured to estimate the duration of the transition as a function of a plurality of supervision timers.

25. (Original) The wireless communication device of claim 23, wherein the first wireless communication system is an IS856 system and the second wireless communication system is an IS2000-1x system.

26. (Original) The wireless communication device of claim 25, wherein the supervision timer is a Control Channel Supervision Timer.

27. (Currently Amended) ~~[[The]]~~ A wireless communication device of claim 26, wherein the interoperation module is configured to:

first wireless communication system hardware for operating in a first wireless communication system;

second wireless communication system hardware for operating in a second wireless communication system;

an interoperation module to configure the wireless communication device in response to a transition between the first and second wireless communication systems, the interoperation module adapted to:

estimate a duration of the transition as a function of a supervision timer,

attempt to receive a synchronous control channel capsule; and

transition to a network acquisition state when the attempt to receive the synchronous control channel capsule is unsuccessful.

28. (Original) The wireless communication device of claim 25, wherein the supervision timer is a data rate control (DRC) supervision timer, and wherein the interoperation module is configured to:

start a combination timer; and

when returning to the IS856 system, estimate the duration of the transition as a function of the DRC supervision timer and the combination timer.

29. (Original) The wireless communication device of claim 28, wherein the interoperation module is configured to:

restart a transmitter in response to expiration of the DRC supervision timer; and
transition to an inactive state in response to expiration of the combination timer.

30. (Currently Amended) An apparatus comprising:
means for starting a timer defined for use within a first wireless communication system; and
means for estimating [[a]] duration of a transition from transitions between the first wireless communication system [[to]] and a second wireless communication system as a function of the timer, each of the wireless communication systems being a voice/data system that conforms to a standard for at least one of CDMA, TDMA, FDMA, and GSM.

31. (Original) The apparatus of claim 30, further comprising means for performing a pre-defined operation associated with the timer.

32. (Original) The apparatus of claim 31, wherein the operation is pre-defined by the first wireless communication system.

33. (Original) The apparatus of claim 30, wherein the timer comprises a supervision timer.

34. (Original) The apparatus of claim 30, wherein the timer is defined by the IS856 wireless communication standard.

35. (Original) The apparatus of claim 34, further comprising:
means for starting a plurality of timers defined for use within the first wireless communication system; and
means for estimating the duration of the transition as a function of the plurality of timers when returning to the first wireless communication system.

36. (Original) The apparatus of claim 30, wherein the first wireless communication system is an IS856 system and the second wireless communication system is an IS2000-1x system.

37. (Currently Amended) The apparatus of claim 36, wherein the ~~supervision~~ timer comprises an IS856 Control Channel Supervision Timer.

38. (Currently Amended) ~~[[The]]~~ An apparatus ~~of claim 37, further~~ comprising:

means for starting an IS856 Control Channel Supervision Timer defined for use within an IS856 communication system;

means for estimating a duration of a transition from the IS856 communication system to an IS2000-1x communication system as a function of the timer;

means for attempting to receive a synchronous control channel capsule; and
means for transitioning to a network acquisition state when the attempt to receive the synchronous control channel capsule is unsuccessful.

39. (Currently Amended) The apparatus of claim 36, wherein the ~~supervision~~ timer comprises a data rate control (DRC) supervision timer, the apparatus further comprising:

means for starting a combination timer; and
means for estimating the duration of the transition as a function of the DRC supervision timer and the combination timer when returning to the IS856 system.

40. (Original) The apparatus of claim 39, further comprising:

means for restarting a transmitter in response to expiration of the DRC supervision timer; and

means for transitioning to an inactive state in response to expiration of the combination timer.

41. (Currently Amended) A system comprising:

a memory that stores processor-readable instructions; and

a processor coupled to the memory that executes the instructions to start a timer defined for use within a first wireless communication system and to estimate ~~[[a]]~~ duration of ~~a transition from~~ transitions between the first wireless communication system ~~[[to]]~~ and a second wireless communication system as a function of the timer, each of the wireless communication systems being a voice/data system that conforms to a standard for at least one of CDMA, TDMA, FDMA, and GSM.

42. (Original) The system of claim 41, wherein the processor further executes the instructions to perform a pre-defined operation associated with the timer.

43. (Original) The system of claim 42, wherein the operation is pre-defined by the first wireless communication system.

44. (Original) The system of claim 41, wherein the timer comprises a supervision timer.

45. (Original) The system of claim 41, wherein the timer is defined by the IS856 wireless communication standard.

46. (Original) The system of claim 41, wherein the processor further executes the instructions to:

start a plurality of timers defined for use within the first wireless communication system; and

when returning to the first wireless communication system, estimate the duration of the transition as a function of the plurality of timers.

47. (Original) The system of claim 41, wherein the first wireless communication system is an IS856 system and the second wireless communication system is an IS2000-1x system.

48. (Currently Amended) The system of claim 47, wherein the ~~supervision~~ timer comprises an IS856 Control Channel Supervision Timer.

49. (Currently Amended) ~~[[The]]~~ A system of claim 48, wherein the processor further executes the instructions to comprising:

a memory that stores processor-readable instructions; and

a processor coupled to the memory that executes the instructions to:

start a timer defined for use within a first wireless communication system;

estimate a duration of a transition from the first wireless communication system to a second wireless communication system as a function of the timer;

attempt to receive a synchronous control channel capsule; and

transition to a network acquisition state when the attempt to receive the synchronous control channel capsule is unsuccessful.

50. (Currently Amended) The system of claim 47, wherein the ~~supervision~~ timer comprises a data rate control (DRC) supervision timer, and wherein the processor further executes the instructions to:

start a combination timer; and

when returning to the IS856 system, estimate the duration of the transition as a function of the DRC supervision timer and the combination timer.

51. (Original) The system of claim 50, wherein the processor further executes the instructions to:

restart a transmitter in response to expiration of the DRC supervision timer; and

transition to an inactive state in response to expiration of the combination timer.

52. (New) The method of claim 8, further comprising:

attempting to receive a synchronous control channel capsule; and

transitioning to a network acquisition state when the attempt to receive the synchronous control channel capsule is unsuccessful.

53. (New) The processor-readable medium of claim 19, containing further instructions for:

attempting to receive a synchronous control channel capsule; and
transitioning to a network acquisition state when the attempt to receive the
synchronous control channel capsule is unsuccessful.

54. (New) The wireless communication device of claim 26, wherein the
interoperation module is configured to:

attempt to receive a synchronous control channel capsule; and
transition to a network acquisition state when the attempt to receive the
synchronous control channel capsule is unsuccessful.

55. (New) The apparatus of claim 37, further comprising:
means for attempting to receive a synchronous control channel capsule; and
means for transitioning to a network acquisition state when the attempt to receive
the synchronous control channel capsule is unsuccessful.

56. (New) The system of claim 48, wherein the processor further executes the
instructions to:

attempt to receive a synchronous control channel capsule; and
transition to a network acquisition state when the attempt to receive the
synchronous control channel capsule is unsuccessful.